

TURBO-TUFF™ RECESS MOUNTED HIGH SPEED HAND DRYER



FEATURES:

- Vandal-resistant – fully recessed so it can't be pulled off the wall
- Fast drying, under 15 seconds
- Owner-adjustable air speed and temperature
- On/off heating options
- Operates automatically using infrared sensor with auto-resetting thermostat
- Type 304 satin finish stainless steel cover
- Accessible compliant

Turbo-Tuff™ Recess Mounted Sensor Hand Dryer shall operate automatically from IR sensor that shall activate dryer when hands are placed in sensor zone. Cover and hand drying chamber shall be 18 gauge type 304 stainless steel alloy 18-8. All exposed surfaces shall have satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge galvanized steel with a 13mm wide perimeter trim to lay flush against wall and shall have concealed and captive hex screws to close cover. Motor and heating element shall have internal resetting automatic thermal protection. Fixed directional air vanes shall be heavy duty, rust proof and tamper resistant. Air intake slots shall not allow access to internal parts. Circuitry shall have self-adjusting time-out and fail-safe off protection controlled by a microprocessor that shall detect and reject false signals and shall automatically self-calibrate to provide uniform sensitivity over its entire life span. Entire unit shall be internally electrically grounded.