



SPECIFICATION

Vertical Soap Dispenser shall hold and dispense up to 1.18 litres of liquid soap and be fabricated of 22 gauge type 304 stainless steel alloy 18-8. Front exposed surface shall be matte black powder coat finish. Valve shall be constructed of a plastic valve body and push button and plastic internal parts. Unit shall have a hinged stainless steel refill door on top of unit, which is opened with special key provided.

INSTALLATION

Unit is surface mounted to wall or partition with a wall mounting plate (supplied) and screws (supplied). Unit is secured to interlocking wedge bracket and locked in place by a screw (supplied) installed through rear wall and accessed thru unlatched hinged refill door. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

SOAP REQUIREMENTS

Proper usage of this dispenser requires, that only soap within the following range for viscosity and pH may be used:

- Viscosity Range (mPa-s or cP): 100 – 3500
- pH Range: 5.5 ~ 8.5


OPERATION

Soap is manually dispensed by depressing push button. Unit is refilled through hinged refill door at top requiring special key (supplied) to open. Soap tank will continue to feed properly until empty. Tank supply is refilled manually on cycle determined by maintenance needs.

WARRANTY

One year.

Surface Mounted Vertical Soap Dispenser – Matte Black shall be Model No. 10-0341-41 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

