



Models shown: 10-7340-S (satin finish) & 10-7340-41 (matte black finish)

SPECIFICATION

Single Robe Hook shall be fabricated of stainless steel alloy 18-8, type 304. Post shall be 22 gauge, 13mm x 25mm rectangular tubing with formed 22 gauge mounting flange and bracket welded on end. Cap plate shall be 14 gauge, 19mm x 32mm with radiused corners and internally welded to outer end. Mounting plate shall be included and shall be 18 gauge. A stainless steel set screw shall be provided on bottom perimeter of flange to lock unit to mounting plate. Surface finish shall be bright, satin or matte black powder coat, as chosen by option and indicated by code suffix.


INSTALLATION

Surface mount unit on door back or wall using two (2) №10 self-tapping screws (by others) through holes provided in mounting plate into suitable prepared mountings (by others) or other suitable mounting hardware (by others) to suit door or wall conditions. Hang post and flange assembly on mounting plate and tighten set screw to lock unit to plate. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

WARRANTY

One year.

Single Robe Hook shall be Model No. 10-7340-B (bright finish), 10-7340-S (satin finish) or 10-7340-41 (matte black powder coat) as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

