



Shown: Model No. 10-74022-HBD



SPECIFICATION

Recessed Dual Roll Toilet Paper Holder with Hood shall hold and dispense all standard core roll tissue up to 152mm in diameter roll and shall be fabricated of stainless steel type 304 alloy 18-8. Each outer shell shall have two (2) perforated lugs for wet wall anchoring or two (2) dimpled holes for dry wall installation. Hoods shall be attached to top of unit with full-length brass pivot rods. Rollers shall be chrome plated high impact resistant ABS plastic and shall be spring-loaded. Mounting style shall be wet wall or dry wall as chosen by option and indicated by code suffix. All exposed surfaces shall be satin or bright finish as chosen by option and indicated by code suffix.

INSTALLATION

For Wet wall Recessed Mounting: Slop grout into rough wall opening. Apply grout to back of unit and on perforated lugs and push unit into opening to seat flange flush with wall face. Allow unit to set and grout to cure before use.

For Standard Dry Wall Recessed Mounting: Use four (4) No 10 stainless steel Philips flat or oval head self-tapping or wood screws (by others) of suitable length to penetrate blocking in back of RWO by approximately 13mm. Apply a continuous bead of silicone sealant (by others) behind flange. Tighten screws to hold flange tight against finished wall face. Wipe off excess sealant immediately.

Optional Method for Dry Wall Recessed Mounting: Order two (2) separate items Model No 39 dry wall clamps. Loosely attach clamps to the back of the unit with four (4) stainless steel Philips flat or oval head No 10B (or 10AB or 10BP) self-tapping screws (provided by others to suit wall conditions) through dimpled holes at back of shell. Apply a continuous bead of silicone sealant (by others) behind flange. Insert into RWO and adjust clamps so that they grip inside wall surface through opening. Secure accessory to clamps and wall by tightening screws. Wipe off excess sealant immediately.

For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

Rough wall opening (RWO) shall be 298mm x 140mm x 51mm.

WARRANTY

One year.

OPTIONS

Optional finish and mounting style must be specified as either bright or satin and wet or dry wall. Specify finish and mounting by adding code suffixes to model number.

| | |
|---------------|---|
| 10-74022-BD | Recessed, Bright Stainless Steel |
| 10-74022-SD | Recessed, Satin Stainless Steel |
| 10-74022-HBD | Recessed, Hooded, Bright Stainless Steel |
| 10-74022-HSD | Recessed, Hooded, Satin Stainless Steel |
| 10-74022-BSM | Surface Mounted, Bright Stainless Steel |
| 10-74022-SSM | Surface Mounted, Satin Stainless Steel |
| 10-74022-HBSM | Surface Mounted, Hooded, Bright Stainless Steel |
| 10-74022-HSSM | Surface Mounted, Hooded, Satin Stainless Steel |

Option-S = Satin.

Option-B = Bright polished finish.

Option-W = Wet wall installation.

Option-D = Dry wall installation.

Double Toilet Roll Holder Recessed with Hood shall be Model No.10-74022-H as supplied by ASI JD MacDonald. (10-39 mounting clamp for dry walls).



All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

