



SPECIFICATION

Frameless Stainless Steel mirror with Masonite back shall be fabricated of alloy 18-8 stainless steel, grade 304, 20 gauge with No. 8 mirror finish. Backing shall be 6mm thick tempered waterproof Masonite. Unit shall have 8mm returns to wall all around. Unit shall have four (4) 5mm diameter mounting holes for sizes up through 610mm x 760mm, sizes 610mm x 910mm and up shall have six (6) mounting holes.

INSTALLATION

Surface mount unit to wall using hardware supplied by installer through four (4) or six (6) mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

DESIGNERS NOTE

The reflective quality of a stainless steel mirror is not as true as plate glass. This mirror is not recommended to be made larger than 1219mm x 610mm because image quality degrades (distortion) with increased surface size.

Frameless Stainless Steel Mirror shall be Model No. 10-8026 as supplied by ASI JD MacDonald.

WARRANTY

One year.

Model No.	Width & Height	Accessible Compliant
10-8026-1620	410 x 510 mm	
10-8026-1624	410 x 610mm	
10-8026-1824	460 x 610mm	
10-8026-1830	460 x 760mm	
10-8026-2430	610 x 760mm	
10-8026-2436	610 x 910mm	
10-8026-2439	610 x 990mm	X

Note: some sizes may require longer lead times for supply than other size

